

## iQ500, Heat Pump Dryer, 9 kg WT47RT90GB



**A++**



### Features

#### Technical Data

Construction type : Freestanding  
 Removable top : No  
 Door Hinge : Right  
 Color / Material housing : White  
 Power cord length (cm) : 145.0  
 Height of removable worktop (mm) : 842  
 Overall appliance dimensions (HxWxD) (mm) : 842 x 598 x 599  
 Net weight (kg) : 49.863  
 Drum volume (l) : 112  
 Fluorinated greenhouse gases : No  
 Type of refrigerant : R290  
 Hermetically sealed equipment : Yes  
 Quantity of fluorinated gases (kg) : 0.120  
 The quantity expressed in CO2 equivalent (t) : 0.000  
 Watts (W) : 1000  
 Current (A) : 10  
 Volts (V) : 220-240  
 Frequency (Hz) : 50  
 Approval certificates : CE, VDE  
 Drying process : automatic  
 Capacity cotton (kg) - NEW (2010/30/EC) : 9.0  
 Standard cotton programme : Cotton cupboard dry  
 Energy efficiency class (2010/30/EC) : A++  
 Energy consumption electric dryer, full load - NEW (2010/30/EC) (kWh) : 2.08  
 Standard cotton programme time at full load (min) : 225  
 Energy consumption electric dryer, partial load - NEW (2010/30/EC) (kWh) : 1.23  
 Standard cotton programme time at partial load (min) : 137  
 Weighted annual energy consumption, electric dryer - NEW (2010/30/EC) (kWh) : 258.0  
 Power consumption in off-mode (W) - NEW (2010/30/EC) : 0.10  
 Power consumption in left-on mode (W) - NEW (2010/30/EC) : 0.75  
 Duration of the left-on mode - NEW (2012/30/EC) (min) : 30  
 Weighted programme time (min) : 175  
 Condensation efficiency class - NEW (2010/30/EC) : B  
 Average condensation efficiency full load (%) : 83  
 Average condensation efficiency partial load (%) : 83  
 Weighted condensation efficiency (%) : 83

### Optional accessories

WZ27410	Stacking kit
WZ27400	Stacking kit with pull-out shelf
WZ20600	Wool in basket - accessory
WZ20160	Condenser drainage kit



## iQ500, Heat Pump Dryer, 9 kg WT47RT90GB

### Line drawings

