

Hob 733430 16421C

USP :

ChildLock

Timer function

Residual heat indicator

Rapid Boil function

Type of control Product group Soft cut hob edges The countdown timer can be set for up to 99 minutes. If the optimum cooking time for a particular dish is known from experience, the timer can be set and the hob will switch off automatically when completed. A beep will signal that the food is ready.

The RapidBoil function intensifies heating, resulting in significantly less heating-up time. Touch control Induction hob

Another bonus is definitely flush installation, which means smooth transition between the hob and the worktop. It is easier to clean and brings a modern, stylish look to your kitchen.

Basic information :

Product group	Нор
Brand	HISENSE
Product name / Commercial code	16421C
Commercial code	733430
EAN code	3838782181429
	3838782181429 Built-in
Construction type	
Control type	
Energy input	Electricity
Total number of positions that can be used at the same time	4
Number of gas burners	
Number of electric cooking zones	4
Number of electric plates	1
Number of radiant plates	1
Number of halogen plates	1
Number of induction plates	4
Number of electric warming zones	4
Location of control panel	Hob front
Basic external material of hob surface	Ceramic Glass
Hob color	Black
Hob frame material	Without frame
Hob edges	/ Bevelled edges
Electrical connection rating	7200 W
Gas connection rating	1
Current	1
Voltage	220-240
Frequency	50/60
Marks of conformity	CE
Plug type	Without plug and supply cord
Width of the product	595 mm
Height of the product	58 mm
Depth of the product	520 mm
Width of the packed product	640 mm
Height of the packed product	160 mm
Depth of the packed product	570 mm
Min height of installation niche	74 mm
Max height of installation niche	1
Min width of installation niche	560 mm
Max width of installation niche	562 mm
Depth of installation niche	490 mm
Net weight	7,6 kg
Gross weight	8,1 kg
Location of control panel	/

Features :

733430

Short description of the product Automatic programmes Location of 1st heating element Type of 1st heating element Dimension of 1st heating element Power of 1st heating element Location of 2nd heating element Type of 2nd heating element Dimension of 2nd heating element Power of 2nd heating element Location of 3rd heating element Type of 3rd heating element Dimension of 3rd heating element Power of 3rd heating element Location of 4th heating element Type of 4th heating element Dimension of 4th heating element Power of 4th heating element Power on indicator Plate on indicator Type of regulation Type of lid Residual heat indicator Main on/off switch Safety device Accessories included Electronic timer

16421C No Front left Induction heating element 210 mm 1500/2000/0 W Rear left Induction heating element 145 mm 1200/1600/0 W Rear right Induction heating element 210 mm 1500/2000/0 W Front right Induction heating element 145 mm 1200/1600/0 W Yes 4 Step energy regulated None Four parts No Yes

Switch-off

