


IAX64411CB



Command water. At a touch

There are more exciting things to do than watching water boil. The 7000 SenseBoil® Induction Hob detects rising bubbles and automatically reduces to a low simmer. So the focus can be fine-tuning those flavours and mastering that menu.

Product Benefits & Features



Boiling water, under control with the Boil Sensor The Boil Sensor detects rising bubbles and automatically adjusts the temperature settings, reducing it to a controlled simmer. No more montioring. Saving both time and energy.



Hob2Hood®: The hands-free hood

The Hob2Hood® function connects the hob and the hood. The cooker hood automatically adjusts the fan speed based on the heat, without lifting a finger. For powerful extraction when searing. And quieter extraction when simmering.



Less steps and more control with Direct Touch Controls

The Direct Touch Controls user interface uses intuitive numbers 1-14 so you can set the right temperature right away without having to toggle through the plus and minus buttons.



Quicker heat for extra speed with PowerBoost

A blast of fast. No more waiting around for pots to boil. The PowerBoost function gives you an instant burst of heat. PowerBoost is perfect for tasks that require you to boil a large pot of water quickly.



Hob timer. Built for precision

The built in hob timer can be set up to one hour, and will automatically power the hob down when it elapses. For effortlessly precise results.

- Minute Minder
- Child Lock
- Hob2Hood®: Control your Cooker Hood via the Hob.
- PowerBoost: The PowerBoost function allows the induction zone to operate at a higher power.
- Pause Function: Take short breaks without losing your cooking settings.
- OptiFix $^{\text{TM}}$: Only one step to install the hob.
- EcoTimer™
- SenseBoil®: Detects rising bubbles and adjusts temperature to a simmer, saving time and energy.



IAX64411CB

Product Specification

Series	7000
Main Colour	Black
Plug or Hardwired	Hardwired connection only
Dimensions (mm) (WxD)	590x520
Built-in Dimensions (mm) (HxWxD)	44x560x490
Cord Length (m)	N/A
LED Colour	Red
Left Front - Power/Diameter	2300/3700W/210mm
Left Rear - Power/Diameter	1800/2800W/180mm
Right Front - Power/Diameter	1400/2500W/145mm
Right Rear - Power/Diameter	1800/2800W/180mm
Gas Supply: Natural Gas	N/A
Gas Replacement	N/A
Product Number (PNC)	All Open
Control Functions	3 step residual heat, Acoustic signal, Booster, Child-lock, Count up timer, Eco timer, Hob-hood connection, Key- lock function, Minute minder, Pause, SenseCook Boil, Sound off, Timer
Pan Support Type	N/A
Number of Cooking Zones	4
Hob Type	Induction Hob
Frame Type	Frameless Square
Hob safety	Automatic Switch Off

