


IKX64441CB





Combine two zones to cook more

The 6000 Bridge Induction Hob can easily cope when you're cooking with bigger pans. The Bridge button links two cooking zones together to fit any large or long pan. The bridged zone will share the same temperature and time setting.

Product Benefits & Features



Combine 2 cooking zones with Bridge

The Bridge function combines two cooking zones together to fit any large or long pan. Sharing the same temperature and time setting, the linked zones are ideal when you're cooking for dinner parties or bigger celebrations.



Hob2Hood®: The hands-free hood

The Hob2Hood® function connects the hob and the hood. The cooker hood automatically adjusts the fan speed based on the heat, without lifting a finger. For powerful extraction when searing. And quieter extraction when simmering.



Less steps and more control with Direct Touch Controls

The Direct Touch Controls user interface uses intuitive numbers 1-14 so you can set the right temperature right away without having to toggle through the plus and minus buttons.



Quicker heat for extra speed with PowerBoost

A blast of fast. No more waiting around for pots to boil. The PowerBoost function gives you an instant burst of heat. PowerBoost is perfect for tasks that require you to boil a large pot of water quickly.



Hob timer. Built for precision

The built in hob timer can be set up to one hour, and will automatically power the hob down when it elapses. For effortlessly precise results.

- Hob2Hood®: Allows you to control the cooker hood via your hob.
- PowerBoost: Gives an instant increase in temperature allowing water to boil in less than 90 seconds.
- The bridging function: Combines 2 cooking zones allowing flexibility for any size pan.
- Pause functionality allows you to take short breaks without losing your cooking settings.
- OptiFix™: Only one step to install the hob.
- EcoTimer™: Saves energy by using the residual heat from the hob, turning off the cooking zone before the end of your timer to boost efficiency.
- Child lock safety function.
- · Minute Minder



IKX64441CB

Product Specification

Series	6000
Main Colour	Black
Plug or Hardwired	Hardwired connection only
Dimensions (mm) (WxD)	590x520
Built-in Dimensions (mm) (HxWxD)	44x560x490
LED Colour	Red
Left Front - Power/Diameter	2300/3200W/210mm
Left Rear - Power/Diameter	2300/3200W/210mm
Right Front - Power/Diameter	1400/2500W/145mm
Right Rear - Power/Diameter	1800/2800W/180mm
Gas Supply: Natural Gas	N/A
Gas Replacement	N/A
Product Number (PNC)	All Open
Control Functions	3 step residual heat, Acoustic signal, Automatic heating-up, Booster, Bridge function, Child-lock, Count up timer, Eco timer, Hob-hood connection, Key- lock function, Minute minder, Pause, Sound off, Timer
Pan Support Type	N/A
Number of Cooking Zones	4
Hob Type	Induction Hob
Frame Type	Frameless Square
Hob Safety	Automatic Switch Off
Total Electricity Loading (W)	7350

