

WPsd 4652

Multi-temperature wine fridge
Vinidor



2 Zones

Temp Protect Plus

Humidity Select

Fresh Air

UV Protect Plus

Vibrate Safe

Steel Interior

LED

Touch Display

Smart Device Ready

← 60 →



| | |
|---------------------------------------|--|
| Energy efficiency class | |
| Energy consump. in 365 days/24 h | 118 / 0.323 kWh ¹ |
| Max. No. of Bordeaux bottles 0.75 Ltr | 107 ² |
| Total volume | 272 l ³ |
| Noise output | 38 dB(A) |
| Climate rating | SN-ST (+10 °C to +38 °C) |
| Door | Glass door with stainless steel frame and SmartSteel |
| Side walls | silver |
| Exterior dimensions in cm (h / w / d) | 145.4 / 59.7 / 67.5 ¹ |
| Controls | |
| Type of Control | LC monochrome display in the door, touch electronic Digital temperature display for both wine zones |
| Alarm in case of malfunction | visual and acoustic |
| Door alarm | visual and acoustic |
| Child proof function | yes |
| Features | |
| Temperature zones | 2 |
| Temperature range | +5 °C to +20 °C |
| Adjustable cooling circuits | 2 |
| Forced air system | Convection cooling, fresh air supply via FreshAir activated charcoal filter |
| Interior light | LED zone lighting permanently on, dimmable |
| Handle | Slimline handle with integrated opening mechanism |
| Interface | SmartDeviceBox: optional accessory |
| Shelf material | Adjustable beech wood shelves |
| Storage shelves | 6 |
| Door hinges | Reversible door hinging, right |
| EAN-Nr. | 4016803087953 |

¹ To achieve the indicated energy consumption level, the wall spacers provided with the appliance must be used. These increase the appliance depth by approximately 3.5 cm. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy consumption level.

² These models are only bound for storing wine. Maximum DIN norm bordeaux bottles capacity (0.75 l) as per norm NF H 35-124 (H: 300.5 mm, Ø 76.1 mm)

³ In accordance with Regulation EU 2019/2016 we indicate the total volume to the nearest integer (rounded off) and the volume of the frozen compartments and refrigeration compartments to one place after the decimal point.