

N 30, GAS HOB, 60 CM, STAINLESS STEEL
T26BR46N0



Optional accessories

Z2402X0	Small pot support
Z32SE10X0	Small pot support

Gas hob with side-mounted controls.

- ✓ Pan Supports - continuous cast-iron finish pan supports for maximum stability and cooking convenience.
- ✓ Sword Knobs - a better feel and easier to operate, the new knob in an attractive design.
- ✓ Stainless steel surface - elegant and sophisticated design.

Features

Technical Data

Product name/family:gas hob w
integrated controls

Construction type: Built-in

Energy input: Gas

Number of cooking zones: 4

Type of control setting devices: sword knobs

Min. required niche size for installation (HxWxD): . . 45 x 560-562 x
480-492 mm

Width of the appliance: 580 mm

Dimensions: 56 x 580 x 510 mm

Dimensions of the packed product (HxWxD): . 141 x 651 x 578 mm

Net weight: 6.9 kg

Gross weight: 7.8 kg

Residual heat indicator:without

Location of control panel:Lateral

Basic surface material: Stainless steel

Color of surface:Stainless steel

Length of electrical supply cord: 100.0 cm

EAN code:4242004187271

Gas connection rating:7400 W

Fuse protection:3 A

Voltage: 220-240 V

Frequency: 60; 50 Hz



N 30, GAS HOB, 60 CM, STAINLESS STEEL T26BR46N0

Features

Design

- Stainless steel surface
- Cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: High-speed burner up to 3 KW (depending on gas type)
- Left rear: Standard burner up to 1.7 KW (depending on gas type)
- Right rear: Standard burner up to 1.7 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 56 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.4 KW

N 30, GAS HOB, 60 CM, STAINLESS STEEL
T26BR46N0

Dimensioned drawings

