


iQ500, Gas hob, 60 cm, Stainless steel
EC6A5HC90



Optional accessories

HZ233440	Wok ring
HZ241110	Small pot support
HZ298105	Simmer plate

The gas hob with stepFlame Technology for precise flame control in nine steps.

- ✓ stepFlame Technology – Precise flame control with nine different settings.
- ✓ This wok burner with up to 3.5 kW of power (depending on gas type) is ideal for a wide variety of foods, even in large quantities.
- ✓ High-quality materials and workmanship – continuous cast-iron pan supports.
- ✓ Biomethane ready – Power your gas hob with renewable biomethane gas.
- ✓ The extremely convenient sword knob makes it easy to control and monitor the power level selected.

Features

Technical Data

Product name/family: gas hob w
integrated controls
Design: Built-in
Source of energy: Gas
Number of cooking zones: 4
Type of control setting devices:sword knobs
Min. required niche size for installation (HxWxD):45 x 560-562 x
480-492 mm
Width of the appliance: 582 mm
Dimensions: 53 x 582 x 520 mm
Dimensions of the packed product (HxWxD): ... 141 x 651 x 578 mm
Weight: 12.2 kg
Gross weight: 13.0 kg
Residual heat indicator:without
Location of control panel: Front
Basic surface material:Stainless steel
Color of surface: Stainless steel
Length of electrical supply cord: 100.0 cm
EAN code:4242003742006
Gas connection rating: 8000 W
Fuse protection:3 A
Nominal power:220-240 V
Frequency:60; 50 Hz



iQ500, Gas hob, 60 cm, Stainless steel EC6A5HC90

Features

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- Step Flame technology - 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner gas hob including:
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 8 KW

iQ500, Gas hob, 60 cm, Stainless steel
EC6A5HC90

Dimensioned drawings

