



### DODITOT SDECIEICA TION RELEASE

G1S-EU/ KS9W09 ssued on: 2024-11-8

	PRODUCT SPECIFIC	Α
	Model: 43P7K-UK/R75P	Ġ
	Version: 1.0	ls
Basic Information		
Product Type	4K QLED TV	Ir
Chassis Platform	RT2875P Platform	s
CPU	CA75*2 + CA55*2 1.3GHz	A
GPU	IMG BXE 650Mhz	D
OS	Android S	D
RAM	DDR4-2666: 2G Bytes	
Stoarge	eMMC5.1 16G Bytes	т
UI Style	Google TV UI + TCL TV UI	В
Launcher Homepages Show	Google Play, Netflix, Youtube, Featured Apps, Source, etc.	A T B A
OSD Language	29 Ianguages: English, Spain, French, German, Italy, Czech, Croatian, Danish, Hungarian, Dutch, Norwegian, Polish, Portuguese, Romanian, Slovak, Slovenian, Serbian, Finnish, Swedish, Turkish, Creek, Bulgarian,	
	Russian,Latvian,Lithuanian,Estonian,	s
TV System	ATV: PAL BG	
. v eyetetti	DTV: DVB-T/T2/C/S/S2	
AV System	PAL, NTSC	В
HDMI & HDCP Version	HDMI1.4 & HDMI2.0&HDMI2.1, HDCP1.4 & HDCP2.2	Р
HDR	HDR10+ Decoding, Dolby Vision	A
Power Supply	AC 220V-240V 50/60Hz	
Power Consumption (TV On)	115W	D
Power Consumption (Standby)	≪0.5W	
ECO Energy Efficiency	Yes	C R V
Certification	CB, HDMI, Dolby Audio, Dolby Vision, Dolby Atmos, DTS: X, BBC	R
Certification	CTS (Google Official Certification), Netflix	V
Internet Link	2.4GHz/5GHz dual-band Wi-Fi 802.11 b/g/n 2T2R	L
	Ethernet Network (RJ45, 10/100M)	
Bluetooth	Bluetooth 5.2	R
LED Indicator	Standby indicator (1-LED, white)	С
	MIC indicator (1-LED, colored)	V

Intelligent Sound	Adaptive Content(on,off)
Speakers	Integrated Speaker Boxes
Audio Power (Watts) Speakers	2x10W
Dolby Atmos	On, Off
Sound Mode	Dynamic, Standard, Movie, Music, Voice, Game, Sport
Audo Delay	0~100
TV Placement	Desk Top, Wall Mount
Balance	0~100
Auto Volume Control	On, Off
Digtal Audio Out	Pass through, PCM, Auto, Off
DTS DRC	On, Off
Special Feature	DTS Virtual:X &Dolby Atmos Audio System
Panel Specificatio	n
Panel Specification	n
Panel Specification Backlight Type	n DLED
Panel Specification Backlight Type Panel Supplier (Open Cell)	n DLED INX
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio	DLED INX 16:9
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch)	DLED INX 16:9 42.5
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution	DLED INX 16:9 42.5 3840×2160
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2)	DLED INX 16:9 42:5 3840×2160 350nit (typ.)
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell)	DLED INX 16:9 42:5 3840×2160 350nit (typ.) 5000:1 (typ.)
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms)	DLED INX 16:9 42:5 3840×2160 350nit (typ.) 5000:1 (typ.) 6.5 (typ.)
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms) Viewing Angle (H/V) (Open Cell)	DLED INX 16:9 42:5 3840×2160 350nit (typ.) 5000:1 (typ.) 6.5 (typ.) 178°/178° (typ.)
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms)	DLED INX 16:9 42:5 3840×2160 350nit (typ.) 5000:1 (typ.) 6.5 (typ.) 178°/178° (typ.) 30,000 (typ.)
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms) Viewing Angle (H/V) (Open Cell) Life Time (hrs) Color	DLED INX 16:9 42:5 3840×2160 350nit (typ.) 5000:1 (typ.) 6.5 (typ.) 178°/178° (typ.)
Panel Specification Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms) Viewing Angle (H/V) (Open Cell) Life Time (hrs)	DLED INX 16:9 42.5 3840×2160 350nit (typ.) 5000:1 (typ.) 6.5 (typ.) 178°/178° (typ.) 30,000 (typ.) 1.07G (8 bit + FRC),

Right Side

\_



# **Basic Function** Google Assistant

Google Assistant	Hands-free voice input via built-in MIC
Initial Setup	Yes, for user setting in TV first start-up.
Instant Power On	A special standby mode for start-up in shorter time.
Bluetooth	Yes, for external bluetooth speaker/soundbar.
Channels Edit	Yes, for TV channel renaming.
Input Setting	For input source device name choice and edit.
Input Method	T-IME, Gboard, Virtual Remote Keyboard
System Update	Yes
HDMI CEC	Yes
Audio Language/MTS/NICAM	Yes
PVR/Timeshift	No
EPG	Yes (for DTV programme only)
Subtitle	Yes (for DTV programme only)
Parental Control	Yes (for DTV programme only)
Others	VRR,AIPQ,AIAQ

Voice input via remote control.

Picture	
Picture Preset	Standard, Sports, Movie, Intelligent
Backlight (Brightness)	0~100
Colour Saturation	0~100
Auto Format	On, Off
Screen Mode	Auto format,Screen mode,Overscan
Overscan	On, Off
Dynamic Brightness	Brightness+,ECO,off
Motion Clarity	On, Off
Advanced Settings	Brightness, Color, Clarity, Motion, Expert calibration
Input Lag	15mS @Game Mode
Special Feature	MEMC (60 Hz)

### **USB Device Media Format**

Music	MP3, MKV, WMA, AVI
Picture	JPEG/PNG/BMP/HEIF codec
Mutilmedia Video/Audio Decoder	H.264, MPG1/2/4, WMV, VC1, VP8, VP9, AV1
Video Format up to	Up to 4K@60Hz
USB Mouse/Key Board	Yes






Google Play Store	Popular apps and games.
YouTube	Android TV version.
Google Play Games	Game platform of Google Play.
Google Play Movies & TV	Watch Google Play Movies & TV on Android TV.
Chrome Cast	To cast favorite entertainment and apps contents from your phone, tablet o laptop right to TV.
Netflix	Watch TV shows and movies online.
Media Center	Video/Music play for USB device.

Operation Manual	English
Remote Control and Batteries	RC833A(with 2 batteries)
Base Stand	Integrated in Package
AC Power Cord	1 pcs

## **Mechanical ID Picture**

Unit: mm





## **Mechanical Key Specification**

Carton Dimensions LxWxH (mm)	1075*122*646
Container Loading20 feet (pcs)	361 (w/o pallet)
Container Loading40 feet (pcs)	741(w/o pallet)
Container Loading40 feet High (pcs)	842 (w/o pallet)
Net Weight with Stand (Kg)	6.7
Net Weight without Stand (Kg)	6.6
Gross Weight with Packaging (Kg)	9

PC HIPS

ABS

Screw Quantity (pcs)	4	
Wall-Mount VES	A Contraction of the second seco	
	WMB33-65	
VESA Mounting		
Wall-Mount VES/ VESA Mounting VESA Hole Pattern (mm) Screw Size	WMB33-65	

M4×25

Correct specifications and appearance depend on the actual model, all specifications are subject to change without prior notice.

Drafted by: Qiu.guo

Speak Mask Back Cover

Base Stand

Approved by:

**Base Stand Specifications** 

Screw Size

