



# PRODUCT SPECIFICATION RELEASE Model: 65V6C-UK/R75PT5S-EU Issued on: 2024-10-26

Version: 1.0

<b>Basic Information</b>	
Product Type	LED TV
Chassis Platform	RT2875P Platform
CPU	CA75*2 + CA55*2 1
GPU	IMG BXE 650Mhz
OS	Android S

CPU	CA75*2 + CA55*2 1.3GHz	
GPU	IMG BXE 650Mhz	
OS	Android S	
RAM	DDR4-2666: 2G Bytes	
Stoarge	eMMC5.1 16G Bytes	
UI Style	Google TV UI + TCL TV UI	
Launcher Homepages Show	Google Play, Netflix, Youtube, Featured Apps, Source, et	
OSD Language	29 languages: English, Spain, French, German, Italy, Czech, Croatian, Danish, Hungarian, Dutch, Norwegian, Polish, Portuguese, Romanian, Slovak, Slovenian, Serbian, Finnish, Swedish, Turkish, Greek, Bulgarian, Russian, Latvian,Lithuanian,Estonian, Ukrainian, Albanian, Macedonian,	
TV System	ATV: PAL BG DTV: DVB-T/T2/C/S/S2	
AV System	PAL, NTSC	
HDMI & HDCP Version	HDMI1.4 & HDMI2.0&HDMI2.1, HDCP1.4 & HDCP2.2	
HDR	HDR10+ Decoding, Dolby Vision	
Power Supply	AC 220V-240V 50/60Hz	
Power Consumption (TV On)	145W	
Power Consumption (Standby)	≤0.5W	
ECO Energy Efficiency	Yes	
Certification	CE, HDMI, Dolby Vision, Dolby Atmos, DTS X	
	CTS (Google Official Certification), Netflix	
Internet Link	2.4GHz/5GHz dual-band Wi-Fi 802.11 b/g/n 2T2R	
	Ethernet Network (RJ45, 10/100M)	
Bluetooth	Bluetooth 5.2	
LED Indicator	Standby indicator (1-LED, white)	

### **Basic Function**

Busie i unetion		
Google Assistant	Voice input via remote control.	
Initial Setup	Yes, for user setting in TV first start-up.	
Instant Power On	A special standby mode for start-up in shorter time.	
Bluetooth	Yes, for external bluetooth speaker/soundbar.	
Channels Edit	Yes, for TV channel renaming.	
Input Setting	For input source device name choice and edit.	
Input Method	T-IME, Gboard, Virtual Remote Keyboard	
System Update	Yes	
HDMI CEC	Yes	
Audio Language/MTS/NICAM	Yes	
PVR/Timeshift	No	
EPG	Yes (for DTV programme only)	
Subtitle	Yes (for DTV programme only)	
Parental Control	Yes (for DTV programme only)	
Others	AIPQ,AIAQ	
Picture		
Intelligent Picture	Adaptive Content(on,off)	
Picture Preset	intelligent,vivid,std,sports,mov,game,pc	
Backlight (Brightness)	0~100	
Colour Saturation	0~100	
Auto Format	On, Off	
Screen Mode	Auto format,Screen mode,Overscan	
Overscan	On, Off	
Dynamic Brightness	Brightness+,ECO,off	
Motion Clarity	On, Off	
Advanced Settings	Brightness,Color,Clarity,Motion,Expert calibration	
Input Lag	15mS @Game Mode	
Special Feature	MEMC (60 Hz),DLG 120Hz	
<b>USB Device Media</b>	Format	
Music	MP3, MKV, WMA, AVI	
Picture	JPEG/PNG/BMP/HEIF codec	
Mutilmedia Video/Audio Decoder	H.264, MPG1/2/4, WMV, VC1, VP8, VP9, AV1	
Video Format up to	Up to 4K@60Hz	
USB Mouse/Key Board	Yes	


Sound	
Intelligent Sound	Adaptive Content(on,off)
Speakers	Integrated Speaker Boxes
Audio Power (Watts) Speakers	2x10W
Dolby Atmos	On, Off
Sound Mode	Dynamic,Standard, Movie, Music, Voice, Game, Sport
Audo Delay	0~100
TV Placement	Desk Top, Wall Mount
Balance	0~100
Auto Volume Control	On, Off
Digtal Audio Out	Pass through, PCM, Auto, Off
DTS DRC	On, Off
Special Feature	DTS Virtual:X &Dolby Atmos
Special Feature Panel Specificati	
Panel Specificati	on
Panel Specificati Backlight Type	ON DLED
Panel Specificati Backlight Type Panel Supplier (Open Cell)	ON DLED CSOT
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch)	ON DLED CSOT 16:9
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution	ON DLED CSOT 16:9 65
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2)	ON DLED CSOT 16:9 65 3840×2160
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell)	ON DLED CSOT 16:9 65 3840×2160 280nit (typ.)
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms)	ON DLED CSOT 16:9 65 3840×2160 280nit (typ.) 5000:1 (typ.)
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio	ON DLED CSOT 16:9 65 3840×2160 280nit (typ.) 5000:1 (typ.) 6.5 (typ.)
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms) Viewing Angle (H/V) (Open Cell)	ON DLED CSOT 16:9 65 3840×2160 280nit (typ.) 5000:1 (typ.) 6.5 (typ.) 178°/178° (typ.)
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms) Viewing Angle (H/V) (Open Cell) Life Time (hrs)	ON           DLED           CSOT           16:9           65           3840×2160           280nit (typ.)           5000:1 (typ.)           6.5 (typ.)           178°/178° (typ.)           30,000 (typ.)
Panel Specificati Backlight Type Panel Supplier (Open Cell) Aspect Ratio Panel Active Size (Inch) Display Resolution Brightness (cd/m2) Contrast Ratio (Open Cell) Response Time (G to G) (ms) Viewing Angle (H/V) (Open Cell) Life Time (hrs) Color	ON           DLED           CSOT           16:9           65           3840×2160           280nit (typ.)           5000:1 (typ.)           6.5 (typ.)           178°/178° (typ.)           30,000 (typ.)           1.07G (8 bit + FRC), YAG

#### **Terminals**

Right Side

Back Side










## Featured Application List

Google Play Store	Popular apps and games.	
YouTube	Android TV version.	
Google Play Games	Game platform of Google Play.	
Google Play Movies & TV	Watch Google Play Movies & TV on Android TV.	
Chrome Cast	To cast favorite entertainment and apps contents from your phone, tablet or laptop right to TV.	
Netflix	Watch TV shows and movies online.	
Media Center	Video/Music play for USB device.	

Essential Accessories			
Operation Manual	English		
Remote Control and Batteries	RC833A(with 2 batteries)		
Base Stand	Integrated in Package		
AC Power Cord	1 pcs		
Other	AV Input Adaper (Optional)		

#### **Mechanical ID Picture**



Mechanical Key Specification		Base Stand Sp	Base Stand Specifications		
Carton Dimensions LxWxH (mr	m) 1608*145*1000	Screw Size	ST4X35		
Container Loading20 feet (pe	cs) 110	Screw Quantity (pcs)	4		
Container Loading40 feet (pe	cs) 234				
Net Weight with Stand (Kg)	12.3	Wall-Mount VESA			
Net Weight without Stand (Kg)	12.2				
Gross Weight with Packaging (	(Kg) 19.2	VESA Mounting	WM32-65		
Material Process		VESA Hole Pattern (mm)	200X200		
		Screw Size	M6X12		
Backboard	metal (SGCC)	Screw Quantity (pcs)	4		
Under the face frame	Plastic(ABS+MF)				
Back Cover	Plastic(PC+ABS)				
Base Stand	Plastic(ABS)				

Correct specifications and appearance depend on the actual model, all specifications are subject to change without prior notice.

Drafted by: Guoqiang Jia

Approved by: